

CARBON DIOXIDE EXTINGUISHERS

50 & 100 lb. CARBON DIOXIDE

Large volume CO2 protection provided in either 50 or 100 lb. (2-50 lb. cylinders) wheeled extinguishers. Rugged construction and easy to operate with a “quick-opening” ‘T’ handle valve and horn mounted shut-off valve. A logical choice in areas where a Class B:C non-contaminating agent is required and makes an excellent choice in settings that require a clean agent.

FEATURES

- Heavy-duty steel carriages
- Quick-opening brass valve
- Squeeze-grip chrome-plated discharge valve
- Reinforced wire-braided hose and shock-resistant horn to reduce static electricity
- Brass hose fittings
- UL/ULC label with QR code
- Large instruction pictogram
- DOT/TC cylinder with quick-opening brass valve
- Clean, non-contaminating odorless gas
- 5-Year Warranty



333

334

SPECIFICATIONS	CARBON DIOXIDE	
MODEL NUMBER	333	334
AGENT TYPE	CARBON DIOXIDE	
UL & ULC RATING	20B:C	
CAPACITY (LBS. / KG)	50 / 22.7	100 / 45.4
SHIPPING WT. (LBS. / KG)	257 / 116.6	461 / 209.3
HEIGHT (IN. / CM)	47 / 119.5	
WIDTH (IN. / CM)	23 / 58.4	
DEPTH (IN. / CM)	48 / 122	
DISCHARGE TIME (SEC.)	44+-5	74+-8
CYLINDER	DOT 3AA2015	DOT 3AA2015
DISCHARGE RANGE (FT. / M)	10 - 15 / 3.04 - 4.57	
OPERATING TEMP. (F / C)	-22° TO +120° / -40° TO +49°	
HOSE LENGTH (FT. / M)	40 / 12.1	
HOSE DIAMETER (IN. / CM)	.5 / 1.27	
WHEELS [SEMI-PNEU] (IN. / CM)	16 X 4 / 40.64 X 10.16	
USCG APPROVED	YES	

CONFORMS TO TEST STANDARDS:

CAN/ULC-S503 - UL 154 &
CAN/ULC-S508 - UL 711