

# WATER

## RUGGED

- 5-Year Manufacturer's Warranty
- Stored Pressure Design
- Polished Stainless Steel Cylinders
- All-metal Valve Construction
- Exclusive Crevice-Free, Butt-Welded Cylinder
- Temperature Range +40°F to 120°F

## USER FRIENDLY

- Maximum Visibility During Discharge
- Large Loop Stainless Steel Pull Pin
- QR Coded and Multilingual Labels

## OPTION

- Model 506B Anti-Freeze Charge

**MODEL 240** utilizes the cooling, soaking, and penetrating effect of a 45-55 foot stream of WATER. The 55-second discharge time makes it very effective for inexperienced operators for use on Class A fires that include combustibles such as wood, cloth, paper and many plastics. This section constructed with a chrome-plated brass valve and polished stainless steel cylinder, which helps eliminate corrosion.

**EXTINGUISHER  
SHIPS EMPTY**



240

**THE MODEL 240 MAY BE FREEZE PROTECTED TO -40°F BY ADDING A MODEL 506B CHARGE**

AGENT TYPE	WATER
DESIGN	Hose & Nozzle
MODEL NUMBER	240
UL & ULC RATING	2A
CAPACITY	2.5 Gal
SHIPPING WT. (LBS)	7.5
HEIGHT (IN.)	24.5
WIDTH (IN.)	9
DEPTH (IN.)	7
RANGE (INITIAL-FT)	45-55
DISCHARGE TIME (SEC.)	55
NOMINAL OPERATING PRESSURE	100 PSIG
INCLUDED BRACKET	Wall

**MANUFACTURED AND TESTED TO UL STANDARDS**  
 COMPLIES WITH NFPA 10 STANDARD  
 ISO-9001/ISO-14001 CERTIFIED UL LISTED

**CONFORMS TO TEST STANDARDS:**  
 CAN/ULC-S507 - UL 626 &  
 CAN/ULC-S508 - UL 711

