

# HIGH PERFORMANCE Z-SERIES WHEELED EXTINGUISHERS



756



758



759

## FEATURES

- Proprietary corrosion-resistant paint process
- Integral lift loops for loading/positioning on board
- Carriage design rests the agent cylinder and hose above ground for protection
- Chrome-plated brass shut-off ball valve with swivel pistol grip
- Separate 3" fill port with chrome-plated brass cap
- 1" x 50' field-repairable hose constructed with brass couplings
- Full fill regardless of the type of chemical used—no "nominal" fill sizes
- Large, easy-to-read pressure gauge with stainless-steel gauge guard
- Wide-footprint wheels at 36" x 6" for easy movement
- 12-Year Warranty

## HIGH-PERFORMANCE 125 & 250 lb. –ABC and PURPLE K Dry Chemical

Just like our hand portable extinguishers, High-Performance Z-Series wheeled extinguishers offer superior reliability, corrosion resistance, and affordable maintenance costs.

SPECIFICATIONS	DRY CHEMICAL		
MODEL NUMBER	756	758	759
AGENT TYPE	ABC	PURPLE K	PURPLE K
UL & ULC RATING	40A:160B:C	160B:C	120B:C
CAPACITY (LBS. / KG)	250 / 113.4		125 / 56.07
SHIPPING WT. (LBS. / KG)	775 / 351.3		400 / 181.4
HEIGHT (IN. / CM)	60 / 152.4		53.5 / 135.9
WIDTH (IN. / CM)	37 / 93.8		34 / 86.3
DEPTH (IN. / CM)	44 / 111.6		38.5 / 97.8
DISCHARGE TIME (SEC.)	50	38	30
CYLINDER	DOT 4BW450	DOT 4BW450	DOT 4BW450
DISCHARGE RANGE (FT. / M)	60 - 80 / 18.19 - 24.26		50 - 55 / 15.24 - 16.26
OPERATING TEMP. (F / C)	-40° TO +120° / -40° TO +49°		
HOSE LENGTH (FT. / M)	50 / 15.24		
HOSE DIAMETER (IN. / CM)	1 / 2.54		
WHEELS [STEEL] (IN. / CM)	36 X 6 / 91.44 X 15.24		
<i>"R" MODEL WITH NON-SPARKING RUBBER TREADS</i>			
FLOW RATE (LBS. / SEC.)	4.8	6.6	5.2
USCG APPROVED	YES		

**CONFORMS TO TEST STANDARDS:**  
CAN/ULC-S504 - UL 299 &  
CAN/ULC-S508 - UL 711

